

TECHSELECT® HYDRAULIC OILS

DESCRIPTION: TechSelect® Hydraulic Oils are superior anti-wear hydraulic and circulating fluids blended with highly refined base oils. These hydraulic oils provide outstanding resistance to sludge formation and exhibit excellent antiwear protection. Rust and oxidation preventive capabilities, including superior demulsibility properties, make these oils rugged, even in high-output systems. These oils also feature excellent vane pump and piston pump performance, anti-foam characteristics and superior hydrolytic stability.

TechSelect® Hydraulic Oils resist deterioration and perform at superior levels, even at high operating temperatures, pressures and speeds and low pour point ensures easy system start-up in cold conditions.

PERFORMANCE Meets or exceeds the following tests and requirements:

BENEFITS:
 AFNOR E 48-603
 B. F. Goodrich - 0152
 Cincinnati Milacron - P-68, P-69, P-70
 Denison - HF-0, HF-1, HF-2
 DIN 51524, Part 2
 Ford - M-6C32
 General Motors - LH-04-1, LH-06-1, LH-15-1
 Jeffrey - #87
 Lee Norse - 100-1
 Racine - Model S, variable volume vane pump
 U.S. Steel - 136, 127
 Vickers - I-286-S, M-2950-S, 35VQ25

**TYPICAL
 PROPERTIES*:**

		ISO 32	ISO 46	ISO 68
Viscosity @ 40°C, cSt	D445	32.9	46.5	68.0
Viscosity @ 100°C, cSt	D445	5.5	6.9	8.5
Viscosity Index	D2270	102	100	95
Flash Point, COC, °C	D92	242	212	220
Flash Point, COC, °F	D92	468	414	428
Pour Point, °C	D97	-34	-30	-24
Pour Point, °F	D97	-30	-22	-11
Color	D1500	1.0	1.0	1.5
Gravity, °API	D4052	31.3	30.4	29.3
Oxidation	D943	5000+	5000+	5000+
Rust Test	D665	Pass	Pass	Pass
Emulsion Test	D1401	40-40-0	40-40-0	40-40-0



* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



Updated: 08/2016

TSUNAW