

TECHSELECT® SHINGLE OIL

DESCRIPTION: TechSelect® Shingle Oil can be used on shingles, shake roofs, wooden fencing, wood siding and log homes. This oil penetrates the wood surface to enhance or replace natural oils and resins leached out by long-term exposure. Although TechSelect® Shingle Oil will not renew wood that is already weather damaged, it will retard the aging process. Not to be used on flat surfaces

**TYPICAL
PROPERTIES*:**

Specific Gravity	ASTM D-1298	0.8
Viscosity @ 40 °C cSt	ASTM D-455	18.6
Flash Point °C	ASTM D-92	156



* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Updated: 03/18



TSSO