

TECHSELECT® FULL SYNTHETIC MOTOR OIL

DESCRIPTION: TECHSELECT® Full Synthetic GF-6 Motor Oil is a high performance synthetic motors oil specially formulated to meet the stringent lubrication requirements of today's engines. This SAE 5W-20 motor oil provides maximum protection against rust, corrosion, acid formation, sludge and varnish while yielding exceptional oxidation and low temperature performance. The API SP Resource Conserving specification protects against low speed pre-ignition and chain wear found in newer modern engines, while maximizing fuel economy. Always follow manufacturer's recommendations for viscosity grade and API Service Category.

APPLICATIONS: TECHSELECT® Full Synthetic SAE 5W-20 Motor Oil meet or exceed the requirements of:

- API SP Resource Conserving /ILSAC GF-6A
- API Service Category: SP, SN PLUS, SN, SM, SL, SJ
- Ford WSS-M2C960-A1
- Ford WSS-M2C945-A/B1
- Toyota Specifications
- Honda Service Fill Specifications
- Mazda Specifications
- FCA Chrysler MS-6395

TYPICAL PROPERTIES*:

		API SP-RC ILSAC GF-6A
SAE Grade		5W-20
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	8.9
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	49.9
Viscosity Index		160
NOACK Volatility, Mass %	ASTM D5800	6
Specific Gravity		0.845
API Gravity		36
Pour Point, °F	ASTM D97	-38
Phosphorus, mass %	ASTM D4951	0.07



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Product	6 Gallon Epak Box
Full Synthetic 5W-20	TS66732

Revised 10/2021
TSFSMO