

TECHSELECT® SYNTHETIC BLEND MOTOR OILS

DESCRIPTION: **TECHSELECT® Synthetic Blend Engine Oils** are blended with highly refined base oils and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins **TECHSELECT® Synthetic Blend Engine Oils** also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

PERFORMANCE BENEFITS: Meets or exceeds the following requirements of GM 6094M, Chrysler MS-6395, Toyota specifications, and Honda service fill specifications. Additionally, Ford WSS-M2C960-A1, WSS-M2C945-A/B1 (SAE 5W-20), Ford WSS-M2C961-A1, WSS-M2C946-A/B1 (SAE 5W-30). All grades meet or exceed API Service Category SP, SN PLUS, SN, SM, SL, or SJ and comply with ILSAC GF-6 requirements.

TYPICAL PROPERTIES*:

		SAE 5W-20	SAE 5W-30	SAE 10W-30
Viscosity @ -30°C, cP	D5293	5000	6100	N/A
Viscosity @ -25°C, cP	D5293	N/A	N/A	5700
Viscosity @ 40°C, cSt	D445	46.0	64.0	68.0
Viscosity @ 100°C, cSt	D445	8.2	10.6	10.4
Viscosity Index	D2270	152	157	140
Flash Point, COC, °C	D92	229	231	231
Flash Point, COC, °F	D92	421	448	448
Pour Point, °C	D97	-40.0	-40.0	-36.0
Pour Point, °F	D97	-40.0	-40.0	-33.0
Color	D1500	3.0	3.0	2.5
Gravity, °API	D4052	32.8	32.6	29.5
HT/ HS, cP	D4683	2.6	3.1	3.0



* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Product	5 Gallon Pail	6 Gallon Epak Box	55 Gallon Drum	Tote	Bulk
Syn Blend 5W-20	TS27259	TS67259	TS17259	TS57259	17259
Syn Blend 5W-30	TS27260	TS67260	TS17260	TS57260	17260
Syn Blend 10W-30	TS27261	TS67261	TS17261	TS57261	17261

Revised 11/2020
TSUNSBPCMO

